

CONTIPLAS



GREY REF.	BLACK REF.	int. Ø mm.	ext. Ø mm.	REEL LENGHT
40207	40207N	9,5	12,5	25
40209	40209N	12	15	25
40211	40211N	15	19	25
40213	40213N	17	21	25
40216	40216N	18,3	22,3	25
40221	40221N	23,8	29	25
40229	40229N	31,3	37,3	25
40236	40236N	40,2	47,7	25
40248	40248N	54	61	25

PVC flexible conduit, grey RAL 7001 or black colour, with rigid spiral. Self-extinguishable. Protection level 7 against mechanical damages. Complete fluid tight, s/UNE 20324

Fitting: FINTER - FINTER-H - FINTERMAS
FINTERMAS-H - FINTERPLAS.

CONTIMET



GREY REF.	BLACK REF.	int. Ø mm.	ext. Ø mm.	REEL LENGHT
40307	40307N	9,5	12,5	25
40309	40309N	11	15,3	25
40311	40311N	14	18,7	25
40313	40313N	15	20,5	25
40316	40316N	17	22,6	25
40321	40321N	22	28,4	25
40329	40329N	30	37,1	25
40336	40336N	39	47,1	25
40348	40348N	50	60,1	25

Galvanised steel conduit , PVC covered, grey RAL 7001 or black colour, adapted to its surfaces. Lightweight, high mechanical resistance. Fluid tight. Self-extinguishable. Protection level 7 against mechanical damages. Standards NF, s/UNE 20324.

Fitting: FINTER - FINTER-H - FINTERMAS - FINTERMAS-H.

CONTIDES



REF.	int. Ø mm.	ext. Ø mm.	REEL LENGTH
40507	9,5	12,4	25
40509	11	15,2	25
40511	14	18,6	25
40513	15	20,4	25
40516	17	22,5	25
40521	22	28,3	25
40529	30	37	25
40536	39	47	25
40548	50	60	25

Galvanised steel conduit. Not fluid tight.
Lightweight, high resistance against
squashing. Protection level 7 against
mechanical damages. s/UNE 20324.

Fitting: FINTER - FINTER-H
FINTERMAS - FINTERMAS-H.

SSU*



REF.	Ø int. mm	Ø ext. mm	PACK.
SSU10	6,8	9	25
SSU12	10,3	13	25
SSU16	13,0	16	25
SSU20	16,9	20,5	25
SSU25	21,1	25	25
SSU32	28,1	32	25
SSU40	37,6	42,5	10
SSU50	48,4	53	10
SSU63	57,5	62,5	10

*Made to order

SSU Stainless steel tube. European standards and measures.

Fittings and accessories consult