



BS EN IEC 61386



FITTINGS

FITTING FLK Black (BL), Grey (GR)

PA66 Straight external thread



Nº	METRIC REF.**	PG REF.	PACK.
7	FLK10-M12	FLK10-PG7	10
9	FLK13-M16	FLK13-PG9	10
11	FLK16-M16	FLK16-PG11	10
11	FLK16-M20	FLK16-PG13	10
-	FLK20-M20*	-	10
16	FLK21-M20	FLK21-PG16	10
-	FLK25-M25*	-	10
21	FLK28-M25	FLK28-PG21	10
29	FLK34-M32	FLK34-PG29	10
36	FLK42-M40	FLK42-PG36	2
36	FLK42-M50	-	2
48	FLK54-M50	FLK54-PG48	1
48	FLK54-M63	-	1

* Made to order
** Locknut included

Technical characteristics:

One quick fit piece	IP rating	IP66
Slim design	Temp. Max.	120°
Anti-vibration and tamper resistant	Temp. Min.	-40°
Can be removed using a screwdriver	Low Fire Hazard	High
Suitable for fine and coarse tube profiles	Free Halogens	Yes
Types 42 and 54 feature 4 teeth for added strength	Rohs	Yes
	Reach	Yes



ELBOW 90°

ELBOW FLK90 Black (BL), Grey (GR)

PA66 90° Elbow external thread



Nº	METRIC REF.**	PG REF.	PACK.
11	FLK16-M16-90	FLK16-PG11-90	10
11	FLK16-M20-90	-	10
16	FLK21-M20-90	FLK21-PG16-90	10
21	FLK28-M25-90	FLK28-PG21-90	10
29	FLK34-M32-90	FLK34-PG29-90	10

**Locknut included

Technical characteristics:

One quick fit piece	IP rating	IP66
Slim design	Temp. Max.	120°
Anti-vibration and tamper resistant	Temp. Min.	-40°
Can be removed using a screwdriver	Low Fire Hazard	High
Suitable for fine and coarse tube profiles	Free Halogens	Yes
	Rohs	Yes
	Reach	Yes



ELBOW 45°

ELBOW FLK45 Black (BL), Grey (GR)

PA66 45° Elbow external thread



Nº	METRIC REF.**	PACK.
11	FLK16-M20-45	10
16	FLK21-M20-45	10
21	FLK28-M25-45	10
29	FLK34-M32-45	10

**Locknut included

Technical characteristics:

One quick fit piece	IP rating	IP66
Slim design	Temp. Max.	120°
Anti-vibration and tamper resistant	Temp. Min.	-40°
Can be removed using a screwdriver	Low Fire Hazard	High
Suitable for fine and coarse tube profiles	Free Halogens	Yes
	Rohs	Yes
	Reach	Yes



BS EN IEC 61386



COUPLERS

COUPLER SWIVEL FLK-FLK Black (BL), Grey (GR)

PA66 one piece, slim, fast fit, coupler to join corrugated conduits



Nº	REF.	PACK.
11	FLK16-FLK16	10
16	FLK21-FLK21	10
21	FLK28-FLK28	10
29	FLK34-FLK34	10

Technical characteristics:

One quick fit piece	IP rating	IP66
Slim design	Temp. Max.	120°
Anti-vibration and tamper resistant	Temp. Min.	-40°
Can be removed using a screwdriver	Low Fire Hazard	High
Suitable for fine and coarse tube profiles	Free Halogens	Yes
	Rohs	Yes
	Reach	Yes