



BS EN IEC 61386



FITTINGS

FITTING FPA Black (BL), Grey (GR)

PA66 Straight external thread



Nº	METRIC REF.**	PG REF.	PACK.
7	FPA10-M12	FPA10-PG7	10
7	FPA10-M16	FPA10-PG9	10
9	FPA13-M12	FPA13-PG7	10
9	FPA13-M16	FPA13-PG9	10
9	FPA13-M20	FPA13-PG11	10
11	FPA16-M16	FPA16-PG9	10
11	FPA16-M20	FPA16-PG11	10
11	-	FPA16-PG13	10
11	-	FPA16-PG16	10
13	FPA18-M20	FPA18-PG13	10
-	FPA20-M20*	-	10
16	-	FPA21-PG13	10
16	FPA21-M20	FPA21-PG16	10
16	FPA21-M25	-	10
21	FPA28-M25	FPA28-PG21	10
21	FPA28-M32	FPA28-PG29	10
29	FPA34-M32	FPA34-PG29	10
29	FPA34-M40	-	10
36	FPA42-M40	FPA42-PG36	2
36	FPA42-M50	-	2
48	FPA54-M50	FPA54-PG42	2
48	FPA54-M63	FPA54-PG48	2
-	FPA67-M63*	FPA67-PG48*	1

** Locknut included - * Made to order
Available in NPT threads and UNEF threads (Consult)

Technical characteristics:

One quick fit piece	IP rating	IP66
Slim design	Temp. Max.	120°
Vibration and shock tested to EN61373 Cat 2	Temp. Min.	-40°
Tamper resistant	Low Fire Hazard	High
Can be removed using a screwdriver	Free Halogens	Yes
Suitable for fine and coarse tube profiles	Rohs	Yes
Complies with EN 45545 HL3 and NFPA	Reach	Yes



ELBOW 90°

ELBOW FPA90

Black (BL), Grey (GR)

PA66 90° Elbow external thread



Nº	METRIC REF.**	PG REF.	PACK.
7	FPA10-M12-90	FPA10-PG7-90	10
9	FPA13-M16-90	FPA13-PG9-90	10
11	FPA16-M16-90	FPA16-PG9-90	10
11	FPA16-M20-90	FPA16-PG11-90	10
11	-	FPA16-PG13-90	10
13	FPA18-M20-90	-	10
16	FPA21-M20-90	FPA21-PG16-90	10
21	FPA28-M25-90	FPA28-PG21-90	10
29	FPA34-M32-90	FPA34-PG29-90	10
36	FPA42-M40-90	FPA42-PG36-90	2
36	FPA42-M50-90	-	2
48	FPA54-M50-90	FPA54-PG48-90	1
48	FPA54-M63-90	-	1
-	FPA67-M63-90*	FPA67-PG48-90*	1

** Locknut included

* Made to order

Available in NPT threads and UNEF threads (Consult)

Technical characteristics:

One quick fit piece	IP rating	IP66
Slim design	Temp. Max.	120°
Vibration and shock tested to EN61373 Cat 2	Temp. Min.	-40°
Tamper resistant	Low Fire Hazard	High
Can be removed using a screwdriver	Free Halogens	Yes
Suitable for fine and coarse tube profiles	Rohs	Yes
Complies with EN 45545 HL3 and NFPA	Reach	Yes
90° elbows have a smooth angle		



BS EN IEC 61386



ELBOW 45°

ELBOW FPA45 Black (BL), Grey (GR)

PA66 45° Elbow external thread



Nº	METRIC REF.**	PG REF.	PACK.
11	FPA16-M20-45	FPA16-PG13-45	10
16	FPA21-M20-45	FPA21-PG13-45	10
16	-	FPA21-PG16-45	10
21	FPA28-M25-45	FPA28-PG21-45	10
29	FPA34-M32-45	FPA34-PG29-45	10
36	FPA42-M50-45	FPA42-PG36-45	2
48	FPA54-M50-45	-	1

** Locknut included
Available in NPT threads and UNEF threads (Consult)

Technical characteristics:

One quick fit piece

Slim design

Vibration and shock tested to EN61373 Cat 2

Tamper resistant

Can be removed using a screwdriver

Suitable for fine and coarse tube profiles

Complies with EN 45545 HL3 and NFPA

45° elbows have a smooth angle

IP rating IP66

Temp. Max. 120°

Temp. Min. -40°

Low Fire Hazard High

Free Halogens Yes

Rohs Yes

Reach Yes



COUPLES

COUPLER SWIVEL FPA-FPA Black (BL), Grey (GR)

PA66 one piece, fast fit, coupler to join corrugated conduits



Nº	METRIC REF.	PACK.
11	FPA16-FPA16	10
16	FPA21-FPA21	10
21	FPA28-FPA28	10
29	FPA34-FPA34	10
36	FPA42-FPA42	2
48	FPA54-FPA54	2

Technical characteristics:

One quick fit piece	IP rating	IP66
Slim design	Temp. Max.	120°
Vibration and shock tested to EN61373 Cat 2	Temp. Min.	-40°
Tamper resistant	Low Fire Hazard	High
Can be removed using a screwdriver	Free Halogens	Yes
Suitable for fine and coarse tube profiles	Rohs	Yes
Complies with EN 45545 HL3 and NFPA	Reach	Yes



FITTINGS

FITTING FPAB Black (BL)

PA66 Straight swivel brass external thread



Nº	METRIC REF.	PG REF.	PACK.
9	FPA13-BM16	FPA13-BPG9	10
11	FPA16-BM16	FPA16-BPG9	10
11	FPA16-BM20	FPA16-BPG11	10
16	FPA21-BM20	FPA21-BPG13	10
16	-	FPA21-BPG16	10
21	FPA28-BM25	FPA28-BPG21	10
29	FPA34-BM32	FPA34-BPG29	10
36	FPA42-BM40	FPA42-BPG36	2
36	FPA42-BM50	-	2
48	FPA54-BM50	FPA54-BPG48*	2
48	FPA54-BM63	-	2
-	FPA67-BM63*	-	1

* Made to order

Technical characteristics:

One quick fit piece	IP rating	IP66
Slim design	Temp. Max.	120°
Vibration and shock tested to EN61373 Cat 2	Temp. Min.	-40°
Tamper resistant	Low Fire Hazard	High
Can be removed using a screwdriver	Free Halogens	Yes
Suitable for fine and coarse tube profiles	Rohs	Yes
Complies with EN 45545 HL3 and NFPA	Reach	Yes
Nickel plated brass swivel thread		



BS EN IEC 61386



FITTINGS

FITTING FPABF Black (BL)

PA66 Straight swivel brass internal thread



Nº	METRIC REF.	PACK.
9	FPA13-BFM16	10
11	FPA16-BFM16	10
11	FPA16-BMF20	10
16	FPA21-BFM20	10
21	FPA18-BFM25	10
29	FPA34-BFM32	10
36	FPA42-BFM40	2
48	FPA54-BFM50	2

Technical characteristics:

One quick fit piece	IP rating	IP66
Slim design	Temp. Max.	120°
Vibration and shock tested to EN61373 Cat 2	Temp. Min.	-40°
Tamper resistant	Low Fire Hazard	High
Can be removed using a screwdriver	Free Halogens	Yes
Suitable for fine and coarse tube profiles	Rohs	Yes
Complies with EN 45545 HL3 and NFPA	Reach	Yes
Nickel plated brass swivel thread		



FITTINGS

FITTING FPABMCG Black (BL)

PA66 Straight swivel brass internal thread + cable gland



Nº	REFERENCE	PACK.
9	FPA13-BM16-CG	10
11	FPA16-BM16-CG	10
11	FPA16-BM20-CG	10
16	FPA21-BM20-CG	10
21	FPA28-BM25-CG	10
29	FPA34-BM32-CG	10
36	FPA42-BM40-CG	2
48	FPA54-BM50-CG	2

PG thread version - Made to order

Technical characteristics:

One quick fit piece	IP rating	IP66
Slim design	Temp. Max.	120°
Vibration and shock tested to EN61373 Cat 2	Temp. Min.	-40°
Tamper resistant	Low Fire Hazard	High
Can be removed using a screwdriver	Free Halogens	Yes
Suitable for fine and coarse tube profiles	Rohs	Yes
Complies with EN 45545 HL3 and NFPA	Reach	Yes
Nickel plated brass swivel thread		



ELBOW 90°

ELBOW FPAB90 Black (BL)

PA66 90° Elbow swivel brass external thread



Nº	METRIC REF.	PG REF.	PACK.
9	FPA13-BM16-90	FPA13-BPG9-90	10
11	FPA16-BM16-90	FPA16-BPG9-90	10
11	FPA16-BM20-90	FPA16-BPG11-90	10
16	FPA21-BM20-90	FPA21-BPG13-90	10
16	-	FPA21-BPG16-90	10
21	FPA28-BM25-90	FPA28-BPG21-90	10
29	FPA34-BM32-90	FPA34-BPG29-90	10
36	FPA42-BM40-90	FPA42-BPG36-90	2
36	FPA42-BM50-90	-	2
48	FPA54-BM50-90	FPA54-BPG48-90*	1
48	FPA54-BM63-90	-	1

* Made to order

Technical characteristics:

One quick fit piece	Nickel plated brass swivel thread	
Slim design	IP rating	IP66
Vibration and shock tested to EN61373 Cat 2	Temp. Max.	120°
Tamper resistant	Temp. Min.	-40°
Can be removed using a screwdriver	Low Fire Hazard	High
Suitable for fine and coarse tube profiles	Free Halogens	Yes
Complies with EN 45545 HL3 and NFPA	Rohs	Yes
90° elbows have a smooth angle	Reach	Yes



ELBOW 90°

ELBOW FPABF90 Black (BL)

PA66 90° Elbow swivel brass internal thread



Nº	METRIC REF.	PACK.
9	FPA13-BFM16-90	10
11	FPA16-BFM16-90	10
11	FPA16-BFM20-90	10
16	FPA21-BFM20-90	10
21	FPA28-BFM25-90	10
29	FPA34-BFM29-90	10
36	FPA42-BFM40-90	2
48	FPA54-BFM50-90	1

Technical characteristics:

One quick fit piece	Nickel plated brass swivel thread
Slim design	IP rating IP66
Vibration and shock tested to EN61373 Cat 2	Temp. Max. 120°
Tamper resistant	Temp. Min. -40°
Can be removed using a screwdriver	Low Fire Hazard High
Suitable for fine and coarse tube profiles	Free Halogens Yes
Complies with EN 45545 HL3 and NFPA	Rohs Yes
90° elbows have a smooth angle	Reach Yes



ELBOW 90°

ELBOW FPABMCG90 Black (BL)

PA66 90° Elbow swivel brass internal thread + cable gland



Nº	METRIC REF.	PACK.
9	FPA13-BM16-CG-90	10
11	FPA16-BM16-CG-90	10
16	FPA16-BM20-CG-90	10
16	FPA21-BM20-CG-90	10
21	FPA28-BM25-CG-90	10
29	FPA34-BM32-CG-90	10
36	FPA42-BM40-CG-90	2
48	FPA54-BM50-CG-90	2

PG thread version - Made to order

Technical characteristics:

One quick fit piece	Nickel plated brass swivel thread	
Slim design	IP rating	IP66
Vibration and shock tested to EN61373 Cat 2	Temp. Max.	120°
Tamper resistant	Temp. Min.	-40°
Can be removed using a screwdriver	Low Fire Hazard	High
Suitable for fine and coarse tube profiles	Free Halogens	Yes
Complies with EN 45545 HL3 and NFPA	Rohs	Yes
90° elbows have a smooth angle	Reach	Yes



ELBOW 45°

ELBOW FPAB45 Black (BL)

PA66 45° Elbow swivel brass external thread



Nº	METRIC REF.	PG REF.	PACK.
11	FPA16-BM16-45	FPA16-BPG13-45	10
11	FPA16-BM20-45	FPA16-BPG16-45	10
16	FPA21-BM20-45	FPA21-BPG13-45	10
16	-	FPA21-BPG16-45	10
21	FPA28-BM25-45	FPA28-BPG21-45	10
29	FPA34-BM32-45	FPA34-BPG29-45	10
36	FPA42-BM40-45	FPA42-BPG36-45	2
36	FPA42-BM50-45	-	2
48	FPA54-BM50-45	FPA54-BPG48-45*	1
48	FPA54-BM63-45	-	1

* Made to order

Technical characteristics:

One quick fit piece	Nickel plated brass swivel thread	
Slim design	IP rating	IP66
Vibration and shock tested to EN61373 Cat 2	Temp. Max.	120°
Tamper resistant	Temp. Min.	-40°
Can be removed using a screwdriver	Low Fire Hazard	High
Suitable for fine and coarse tube profiles	Free Halogens	Yes
Complies with EN 45545 HL3 and NFPA	Rohs	Yes
45° elbows have a smooth angle	Reach	Yes



ELBOW 45°

ELBOW FPABF45 Black (BL)

PA66 45° Elbow swivel brass internal thread



Nº	METRIC REF.	PACK.
11	FPA16-BFM20-45	10
16	FPA21-BFM20-45	10
21	FPA28-BFM28-45	10
29	FPA34-BFM32-45	10
36	FPA42-BFM40-45	2
48	FPA54-BFM50-45	1

Technical characteristics:

One quick fit piece	Nickel plated brass swivel thread	
Slim design	IP rating	IP66
Vibration and shock tested to EN61373 Cat 2	Temp. Max.	120°
Tamper resistant	Temp. Min.	-40°
Can be removed using a screwdriver	Low Fire Hazard	High
Suitable for fine and coarse tube profiles	Free Halogens	Yes
Complies with EN 45545 HL3 and NFPA	Rohs	Yes
45° elbows have a smooth angle	Reach	Yes



ELBOW 45°

ELBOW FPABMCG45 Black (BL)

PA66 45° Elbow swivel brass internal thread + cable gland



Nº	METRIC REF.	PACK.
11	FPA16-BM20-CG-45	10
16	FPA21-BM20-CG-45	10
21	FPA28-BM25-CG-45	10
29	FPA34-BM32-CG-45	10
36	FPA42-BM40-CG-45	2
48	FPA54-BM50-CG-45	2

PG thread version - Made to order

Technical characteristics:

One quick fit piece	Nickel plated brass swivel thread	
Slim design	IP rating	IP66
Vibration and shock tested to EN61373 Cat 2	Temp. Max.	120°
Tamper resistant	Temp. Min.	-40°
Can be removed using a screwdriver	Low Fire Hazard	High
Suitable for fine and coarse tube profiles	Free Halogens	Yes
Complies with EN 45545 HL3 and NFPA	Rohs	Yes
45° elbows have a smooth angle	Reach	Yes